

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr




Mute

VK/04562/120/G/W/DA



MUTE, Acoustic Led Lights Up/Down. 3000K. 45W. 6.300lm (Up 2.100lm, Down 4.200lm). Up 130°/Down 65°, CRI>80. IP20, Dimmable DALI, Grey

IP20 DALI   CE

Dimensions	Gallery	Downloads
	   	  

Technical Specifications	
Kelvin	3000K
Power	45W
Voltage	220-240V
Extra	Soundproof LED lighting
Fitting	Ceiling-Pendant
Type	Acoustic Led Lights Up/Down
Safety class	
Light source	Samsung 2835
IP Rating	IP20
CRI	CRI>80
Dimmable	
Lifetime	50.000hrs
Driver	BOKE Dali (included)
Cable Length	1.5m
Working temperature	-20°C - 40°C
PAGE	550 Technical 2024
NICKNAME	Mute

Physical Specifications	
Cable	Black fabric
Color	Grey
Material	Polyester Fiber Acoustic + Aluminium Alloy
Width	30cm
Length	120cm
Height	6.4cm
Net weight of product (kg)	5.25
Gross weight with inner box (kg)	6.75
Width (inner box)	40cm
Length (inner box)	127.5cm
Height (inner box)	10.5cm

Illumination Data	
Lumen	6.300lm (Up 2.100lm, Down 4.200lm)
Beam angle	Up 130°/Down 65°
Lighting direction	

Packing Info	
Pcs/carton	1pc

Certification & Warranty	
Guarantee	3 years

Energy Label

ENERGY

VK LEADING LIGHT
VK/04562/120/G/W/DA

A

B

C

D

E

F

G

D

45
kWh/1000h



2019/2015