



SKU	: 144BB92734GOF0
Housing Material	: Aluminum Die Cast
Housing Colour	: Black (RAL 9005)
Luminaire Dimension [mm]	: Ø78mm
Cut-Out [mm]	: Ø70mm
Optic	: Reflector
Reflector Colour	: Gold
Beam Angle [deg]	: 34°
System Power [W]	: 7W
Luminous Flux [lm]	: 490lm
System Efficiency [lm/W]	: 70lm/W
Light Source	: 927 (2700K / CRI90)
CCT [K]	: 2700K
CRI [Ra]	: 90
Chromaticity Tolerance	: 3 MacAdam
Mains Voltage [VAc]	: 220-240V / 50-60Hz
Power Supply	: Included ON/OFF
Ambient Temperature [degC]	: 35°C
Ingress Protection	: IP20
Light Source Energy Class	: F
Light Source Identifier	: CLU701-1002C4-273H5K2

Lifetime/Failure Rate [h]	: 50000h
Electrical Safety Class	: Class II
Net Weight [Kg]	: 0.35kg
Certificates/Declarations	: CE/UKCA
Warranty [Y]	: 5Y

All rated values @ ambient temperature of 25° C. Electric and photometric values are initially subject to a tolerance of +/- 10%. Tolerance of color temperature +/- 150K.
Technical data can change without prior notice.